

Dampremy

7771N2TF1



Flame retardant fleece

The flame retardant Dampremy fleece ensures a warm, cosy feeling all winter long. The soft, breathable fabric has undergone an anti-pilling treatment. The fleece can be zipped in to several jackets, and is finished with a standing collar, a zipper, two outer pockets, one inside pocket, elastics in the sleeve ends and an elastic cord in the hem.



Flame retardant fleece

Dampremy - 7771N2TF1

European Standards: *(based upon size L)*

- » EN ISO 14116 : 2015 / Outer : IND. 1 - Inner : IND.3
- » EN 14058 : 2017 / Class 11 xx
- » EN ISO 13688 : 2013

Exterior:

- » Straight collar
- » Hidden zip closure
- » 2 inset pockets with zip closure
- » Round sleeves
- » Elastic at end of sleeves
- » Elastic drawstring in hem
- » Back length 75 cm (L)

Interior:

- » Fixed flame retardant cotton lining
- » 1 inside pocket

Fabric:

Double sided fleece: 100% flame retardant polyester; ± 275 g/m²

Sizes:

S - XXXL

Colour:

- » B75 Navy Blue


I.L.S.:

3074 – 7237 – 9728

Packaging:

5 pieces per box

Wash and care instructions:



SIOEN head office

Fabriekstraat 23

B-8850 Ardoonie

Belgium

T: +32 (51) 740 800

F: +32 (51) 740 962

www.sioen-ppc.com



Discover
our products

© 2020 Sioen Apparel - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the Sioen Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice. All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.