

Kassel


4279A2FEO



FLEXOTHANE[®]
ESSENTIAL

Hi-vis rain jacket

A hi-vis rain coat that weighs little, is low-noise and is comfortable? The Kassel is all that, and protects you against the wind and the rain. For extra comfort, back ventilation and a sleeve narrowing mechanism are provided. In addition, you can zip different linings and fleeces on the inside, making it suitable for different seasons.



Hi-vis rain jacket

Kassel - 4279A2FE0

European Standards: *(based upon size L)*

- » EN ISO 20471 : 2013 +A1 2016 / Class 3
- » EN 343 : 2019 / Class 4-1-X
- » EN ISO 13688 : 2013

Exterior:

- » Straight collar
- » Foldaway hood in collar
- » Zip closure under flap with press studs
- » 2 inset pockets
- » Raglan sleeves
- » Sleeve narrowing by press studs
- » Back ventilation
- » Rain gutter
- » Back length 88 cm (S-3XL)

Interior:

- » Different linings/fleeces can be zipped in

Fabric:

Flexothane® Essential: 100% polyester knitting with PU coating; ± 170 g/m²

Sizes:

S - XXXL

Colour:

- » FC1 Hi-Vis Orange
- » FY1 Hi-Vis Yellow

Combining products:

6361 – 6361 – 6623

I.L.S.:

7789

Packaging:

15 pieces per box

Wash and care instructions:



SIOEN head office

Fabriekstraat 23

B-8850 Ardoorie

Belgium

T: +32 (51) 740 800

F: +32 (51) 740 962

www.sioen-ppc.com



Discover
our products

© 2020 Sioen Apparel - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the Sioen Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice. All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.