

Tortolas

443ZA2TJB



Fleece jacket

The Tortolas offers you excellent cold protection as it complies to EN 14058 and has a back length of 72cm (L). Its nice elastic piping finishing at the end of the sleeves gives the jacket a modern look. This soft fleece jacket has also undergone an anti-pilling treatment and is equipped with one chest pocket and two inset pockets on the outside with zip closures. The drawstring in the hem and the two inside pockets are handy extra's.



Fleece jacket

Tortolas - 443ZA2TJB

European Standards: *(based upon size L)*

- » EN 14058 : 2017 / Class 11 xx
- » EN ISO 13688 : 2013

Exterior:

- » Straight collar
- » Hidden zip closure
- » 1 inset chest pocket with zip closure
- » 2 inset pockets with zip closure
- » Round sleeves
- » Elastic piping at end of sleeves
- » Drawstring in hem
- » Back length 72 cm (L)

Interior:

- » 2 inside pockets

Fabric:

2-layer bonded fleece: polyester fleece + polyester fleece; 2 sides brushed; 1 side antipilling; ± 320 g/m²

Sizes:

S - XXXL

Colour:

- » B95 Navy Blue

Packaging:

10 pieces per box

Wash and care instructions:



SIOEN head office

Fabriekstraat 23
B-8850 Ardoonie
Belgium

T: +32 (51) 740 800

F: +32 (51) 740 962

www.sioen-ppc.com



Discover
our products

© 2020 Sioen Apparel - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the Sioen Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice. All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.