

# Monoray


198AA2X98



**SICOPOR**  
REGULAR

## Hi-vis rain jacket

The Monoray is a light hi-vis raincoat, perfect to wear in warmer weather. The Monoray is equipped with a fixed hood and underarm ventilation, and can be combined with Bitoray and Abado hi-vis rain trousers.



# Hi-vis rain jacket

**Monoray - 198AA2X98**

**European Standards:** (based upon size L)

- » EN ISO 20471 : 2013 +A1 2016 / Class 3
- » EN 343 : 2019 / Class 3-4-X
- » EN ISO 13688 : 2013

**Exterior:**

- » Fixed hood
- » Zip closure under flap with press studs
- » 2 patched pockets
- » Round sleeves
- » Sleeve narrowing by press studs
- » Underarm ventilation
- » Back length 85 cm (L)

**Interior:**

- » Fixed lining: mesh in body and polyester in sleeves

**Fabric:**

SIOPOR® Regular: 100% polyester fabric (plain weave) with 100% PU coating; ± 155g/m<sup>2</sup>

**Sizes:**

S - XXXL

**Colour:**

- » FC1 Hi-Vis Orange
- » FR1 Hi-Vis Red
- » FY1 Hi-Vis Yellow

**Combining products:**

199A

**Packaging:**

10 pieces per box

**Wash and care instructions:**



**SIOEN head office**

Fabriekstraat 23  
B-8850 Ardoonie  
Belgium

T: +32 (51) 740 800

F: +32 (51) 740 962

[www.sioen-ppc.com](http://www.sioen-ppc.com)



Discover  
our products

© 2020 Sioen Apparel - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the Sioen Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice. All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.