







# Sweater with ARC protection

With the Druten sweater you will feel comfortable even in hazardous working situations as it provides protection against the risks of electrical flashover, against heat and flame, flamespread and static electricity. This navy sweater is finished with a small stripe segmented reflective tape and 2 side pockets with zip closure.









## Sweater with ARC protection

#### Druten - 635AA2MR3

European Standards: (based upon size L)

» IEC 61482-2 : 2018 APC1 - ATPV 14,8 cal/cm<sup>2</sup>

EN ISO 11612 : 2015 / A1 B1 C1 F1EN ISO 14116 : 2015 / IND.3

» EN 1149-5 : 2018» EN ISO 13688 : 2013

#### **Exterior:**

- » Straight collar
- » Zip closure with inside flap with chin protection
- » 2 inset pockets with zip closure and with flap
- » 1 patched phone pocket on the left sleeve
- » Round sleeves
- » Knitted wind cuffs at end of sleeves
- » Elasticated waist

#### Fabric:

55% modacrylic + 43% cotton + 2% AST; ± 300 g/m<sup>2</sup>

#### Sizes:

S - XXXL

#### Colour:

» B75 Navy Blue

## Packaging:

10 pieces per box

## Wash and care instructions:











## SIOEN head office

Fabriekstraat 23 B-8850 Ardooie Belgium T: +32 (51) 740 800 F: +32 (51) 740 962 www.sioen-ppc.com



Discover our products

© 2020 Sioen Apparel - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the Sioen Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice.

All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.